


Datasheet

<p>Column Speaker</p>	<p style="text-align: center;">SIP-S31E</p> 
<p>Protocol</p>	<p>SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP</p>
<p>Codec</p>	<p>OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz</p>
<p>Network Interface</p>	<p>RJ45, 10BASE-T/100BASE-TX</p>
<p>Operating Temperature</p>	<p>-30°C — +60°C</p>
<p>Operating Humidity</p>	<p>5%-85%</p>
<p>Power</p>	<p>DC 12V/24V</p>
<p>Rated Power</p>	<p>80W</p>
<p>Max SPL</p>	<p>116dB</p>
<p>Frequency Range</p>	<p>130Hz - 16kHz</p>
<p>Harmonic Distortion</p>	<p>0.1@1kHz</p>
<p>Signal to Noise Ratio</p>	<p>91dB</p>
<p>Type</p>	<p>Wall Mounted</p>
<p>Material</p>	<p>Aluminium Alloy</p>
<p>Function</p>	<p>Compatible with VoIP devices and ONVIF VMS, pre-recorded messages, schedule play, HTTP control</p>
<p>Net Weight</p>	<p>8.6KG</p>
<p>Product Size</p>	<p>952x227x125 mm</p>